

# **Hazardous Substance, NON-Dangerous Goods**

## 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

# Product name: Selleys Roof & Gutter Silicone Sealant

Synonyms:	Product Code	Bar Code
Selleys Roof & Gutter Translucent, 75g	930069710013901	9300697100139
Selleys Roof & Gutter Translucent, 310g	930069710039903	9300697100399
Selleys Roof & Gutter Translucent, 310g Triple PK	930069711120302	9300697111203
Selleys Roof & Gutter Translucent, 310g 6PK	930069712268101	9300697122681
Selleys Roof & Gutter Black, 310g	930069711560702	9300697115607
Selleys Roof & Gutter Grey, 310g	930069711561402	9300697115614
Selleys Roof & Gutter Woodland Grey, 300g	930069712251302	9300697122513
Selleys Roof & Gutter Classic Cream, 300g	930069712252002	9300697122520
Selleys Roof & Gutter Galvan Grey, 300g	930069712253702	9300697122537
Selleys Roof & Gutter Navy, 300g	930069712254402	9300697122544
Selleys Roof & Gutter Off White, 300g	930069712255102	9300697122551
Selleys Roof & Gutter White, 300g	930069712256802	9300697122568
Selleys Roof & Gutter Manor Red, 300g	930069712263602	9300697122636
Selleys Roof & Gutter Brown, 300g	930069712264302	9300697122643
Selleys Roof & Gutter Cottage Green, 300g	930069712265002	9300697122650

Recommended use: Metal to metal sealant for steel and aluminium roofing, flashings, guttering, etc.

**Supplier:** Selleys, a division of

DuluxGroup (Australia) Pty Ltd

**ABN:** 67 000 049 427

Street Address: 1956 Dandenong Road

Clayton VIC 3168

Australia

**Telephone:** 1300 555 205

Emergency telephone number: Australia – 1800 033 111 New Zealand – 0800 734 607

## 2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



## Signal Word

Warning

## **Hazard Classification**

Skin Corrosion/Irritation – Category 2 Serious Eye Damage/Irritation – Category 2A Sensitisation – Skin – Category 1A

## **Hazard Statement(s)**

H315 Causes skin irritation

H317 May cause an allergic skin reaction

Product name: Selleys Roof & Gutter Silicone Sealant SDS No: SELGHSEN000411

Issued: 7 April 2016 Version: 5.0 Page: 1 of 7



H319 Causes serious eye irritation

## **Prevention Precautionary Statement(s)**

P102 Keep out of reach of children P103 Read label before use

P210 Keep away from all sources of ignition - No smoking

P261 Avoid breathing mist, vapours or spray

P264 Wash hands, face and all exposed skin thoroughly after handling
P272 Contaminated work clothing should not be allowed out of the workplace

P280 Wear protective clothing, gloves, eye/face protection and suitable respirator as required

### Response Precautionary Statement(s)

P101 If medical advice is needed, have product container or label at hand

P302+352 IF ON SKIN: Wash with soap and water P363 Wash contaminated clothing before reuse

P333+313 If skin irritation or a rash occurs: Get medical advice/attention

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if

present and easy to do - continue rinsing

P337+313 If eye irritation persists get medical advice/attention

P370+378 In case of fire: Use water fog, foam or dry agents for extinction

## **Storage Precautionary Statement(s)**

P403+235 Store in a well ventilated place. Keep cool

# **Disposal Precautionary Statement(s)**

P501 Dispose of contents/container in accordance with local, regional, national and international

regulations

Poisons Schedule (Aust): Not applicable

## DANGEROUS GOODS CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

# 3. COMPOSITION INFORMATION

CHEMICAL ENTITY CAS NO. PROPORTION

Organopolysiloxane mixture - 100%

## 4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

**Inhalation:** Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

**Skin contact:** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Product name: Selleys Roof & Gutter Silicone Sealant SDS No: SELGHSEN000411

Issued: 7 April 2016 Version: 5.0 Page: 2 of 7



**Eye contact:** If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

**Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

**PPE for First Aiders:** Wear overalls, chemical goggles and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

Hazchem Code: Not applicable.

**Suitable extinguishing media:** If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible material.

**Fire fighting further advice:** On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

## **6. ACCIDENTAL RELEASE MEASURES**

#### **SMALL SPILLS**

Wear protective equipment to prevent skin and eye contamination. Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

#### LARGE SPILLS

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

Dangerous Goods – Initial Emergency Response Guide No: Not applicable.

## 7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact and inhalation of vapour.

**Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Store away from sources of heat or ignition. Keep containers closed when not in use - check regularly for leaks.

Product name: Selleys Roof & Gutter Silicone Sealant SDS No: SELGHSEN000411

Issued: 7 April 2016 Version: 5.0 Page: 3 of 7



### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

**National occupational exposure limits:** No value assigned for this specific material by Safe Work Australia or Department of Labour New Zealand.

**Biological Limit Values:** As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures: Use only in well ventilated areas. Keep containers closed when not in use.

**Personal protection equipment:** BLUE: OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.

#### MANUFACTURING, PACKAGING AND TRANSPORT:

Wear overalls, chemical goggles and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

If risk of inhalation of exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

## RECOMMENDATIONS FOR CONSUMER USE:

Wear safety glasses and gloves. Wash hands after use.

**Hygiene measures:** Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with skin and eyes and inhalation of vapour. Ensure that eyewash stations and safety showers are close to the workstation location.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Coloured paste with a mild, characteristic odour.

**Solubility:** Insoluble in water. Uncured material is soluble in organic

solvents. No solvent known for cured sealant.

Specific Gravity (23 ℃): 1.04 Relative Vapour Density (air=1): >1 Vapour Pressure (20 ℃): N Av Flash Point (℃): 63 Flammability Limits (%): N Av Autoignition Temperature (℃): 450 Melting Point/Range (℃): N Av Boiling Point/Range (℃): N Av % Volatile by Volume: N Av N Av pH:

**Viscosity (40 ℃):** >21 mm<sup>2</sup>/sec

**Evaporation Rate (n-Butyl acetate=1):** N Av **Total VOC (g/Litre):** N Av

 $( \mbox{Typical values only - consult specification sheet} ) \\ \mbox{N Av} = \mbox{Not available} \\ \mbox{N App} = \mbox{Not applicable}$ 

Product name: Selleys Roof & Gutter Silicone Sealant SDS No: SELGHSEN000411

Issued: 7 April 2016 Version: 5.0 Page: 4 of 7



### 10. STABILITY AND REACTIVITY

Reactivity: Upon curing or hardening the product will release methyl ethyl ketoxime.

Chemical stability: This material is thermally stable when stored and used as directed.

Hazardous reactions: No known hazardous reactions.

**Conditions to avoid:** Elevated temperatures and sources of ignition.

**Incompatible materials:** Oxidising agents.

**Hazardous decomposition products:** Oxides of carbon and nitrogen, smoke and other toxic fumes. Methyl

ethyl ketoxime.

### 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

#### **Acute Effects**

**Inhalation:** Material may be an irritant to mucous membranes and respiratory tract.

**Skin contact:** Contact with skin will result in irritation. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

**Ingestion:** Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: An eye irritant.

### **Acute toxicity**

Inhalation: This material has been classified as non-hazardous.

**Skin contact:** This material has been classified as non-hazardous.

**Ingestion:** This material has been classified as non-hazardous.

Corrosion/Irritancy: Eye: this material has been classified as a Category 2A Hazard (reversible effects to

eyes).

Skin: this material has been classified as a Category 2 Hazard (irritant to skin).

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser.

Skin: this material has been classified as a Category 1A Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure): This material has been classified as non-hazardous.

Product name: Selleys Roof & Gutter Silicone Sealant SDS No: SELGHSEN000411

Issued: 7 April 2016 Version: 5.0 Page: 5 of 7



**Chronic Toxicity** 

**Mutagenicity:** This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

## 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Acute aquatic hazard:** No information is available to complete an assessment.

Long-term aquatic hazard: No information is available to complete an assessment.

**Ecotoxicity:** No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

**Mobility:** Low mobility in soil. Product cures on contact with air.

## 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

# 14. TRANSPORT INFORMATION

## **ROAD AND RAIL TRANSPORT**

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

## MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

## AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Product name: Selleys Roof & Gutter Silicone Sealant SDS No: SELGHSEN000411

Issued: 7 April 2016 Version: 5.0 Page: 6 of 7



### 15. REGULATORY INFORMATION

## This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)
Basel Convention (Hazardous Waste)
International Convention for the Prevention of Pollution from Ships (MARPOL)

## This material/constituent(s) is covered by the following requirements:

 All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

## **16. OTHER INFORMATION**

## Literary reference

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Reason(s) For Issue: Format change

Minor Text Changes.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since DuluxGroup (Australia) Pty Ltd and DuluxGroup (New Zealand) Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

Product name: Selleys Roof & Gutter Silicone Sealant SDS No: SELGHSEN000411

Issued: 7 April 2016 Version: 5.0 Page: 7 of 7